



**NOTES:**

1. EACH WASH PLUG ASSEMBLY IS INDIVIDUALLY CLEANED, THEN PACKAGED IN AN ANTI-STATIC BAG.
2. MINIMUM WASH PLUG RETENTION FORCE IN RECEPTACLE = 1.5 LBS, IN DIRECTION SHOWN.

**USCONEC LTD. PROPRIETARY**  
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

**Material:** SEE CHART

REV	DATE	DESCRIPTION	ECN
G	6/12/03	UPDATED VIEWS TO REM TAPER FROM ITEM 2 RECESS: ADDED "MATL." COLUMN TO PARTS LIST	00438
H	10/26/06	REVISED MATERIAL	00799
I	9/28/07	REMOVED LOGO, UPDATED PARTS LIST	00904
J1	3/12/13	ADDED 7.0 REC. POCKET DIM.; ADDED NOTE 2	01566
J	4/16/13	RELEASE	01566

**CUSTOMER DRAWING**

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION

**METRIC/mm**

▲ DENOTES CRITICAL DIMENSION

Hickory, NC  
800-769-0944  
[www.usconec.com](http://www.usconec.com)

**USCONEC**

TITLE: **ASSY, WASHPLUG-BLACK /HOLDER**

SIZE: S&M Part No.: **Y0320** DWG NO: **C10212** REV: **J**

SCALE: N.T.S. Drafter: **T HALL** Date: **3/8/2002** SHEET: **1** OF **1**

Parts List				
ITEM	QTY	P/N	DESCRIPTION	MATERIAL
1	1	8351	RECEPTACLE - WASH/DUST PLUG, BLACK	GLASS FILLED PBT
2	1	8851	WASH PLUG	C10919