



NOTES:

1. DIMENSION (5.05±0.05) TO BE HELD FOR LENGTH OF 0.3MIN FROM FRONT SHOULDER. REMAINDER TO BE FLUSH OR BELOW SURFACE , DOWN TO 4.5 MIN.
2. FIBER HOLE ECCENTRICITY : 1.3µm MAX
FIBER HOLE TILT : 0.5° MAX
3. MATERIAL : POLY PHENYLENE SULFIDE

▲ DENOTES CRITICAL DIMENSION

USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material:

REV	DATE	DESCRIPTION	ECN
B	4/24/01	REVISED S & M PART NO.	00066
C	8/21/01	REV 4.40 TRUE POSITION TOL FROM 0.005 TO 0.05	00135

CUSTOMER DRAWING

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION

METRIC/mm

USCONEC
Hickory, NC
800-769-0944
www.usconec.com

TITLE
MINI MT FERRULE 2F SM,
PPS

SIZE	S&M Part No.:	DWG NO.	REV
B	5164	C10372	C
SCALE	Drafter	Date:	SHEET
N.T.S.	MCB	10/10/2000	1 OF 1