



- NOTE:
1. SPRING ENDS GROUND
 2. WHEN COMPRESSED TO 7mm LENGTH, SPRING FORCE = 13 NEWTONS.

USCONEC LTD. PROPRIETARY
 THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: STAINLESS STEEL

REV	DATE	DESCRIPTION	ECN
B	5/20/03	DIM 3.40 WAS 3.50	00361
C	9/26/03	UPDATED VIEWS TO SHOW GROUND ENDS. ADDED NOTES AND DIM Ø0.5, REM DIM 12.0	00470
D1	10/5/15	ADD DIM 4.24 & DEL DIM Ø0.5, REVISED NOTES; ADD DIM 13; DIM 5.35 W 5.4	1835-mm
D	10/16/15	RELEASE	1835-mm
E1	4/7/16	4.23 W 4.24	1916-mm
E	4/26/16	RELEASE	1916-mm

CUSTOMER DRAWING

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION

METRIC/mm

▲ DENOTES CRITICAL DIMENSION

Hickory, NC
800-769-0944
www.usconec.com

USCONEC

TITLE
**SPRING, MTP®,
HIGH FIBER COUNT**

SIZE	S&M Part No.:	DWG NO.	REV
B	Y0367	C10489	E
SCALE	Drafter	Date:	SHEET
N.T.S.	F. COPE	3/10/2003	1 OF 1