



- NOTES:
1. DIMENSION TO BE HELD FOR LENGTH OF 0.3MIN FROM FRONT SHOULDER. REMAINDER TO BE FLUSH OR BELOW SURFACE, DOWN TO 6.45 MIN.
  2. FIBER HOLE ECCENTRICITY : 1.3µm MAX (NOT INCLUDING Y OFFSET : 0.5µm)  
FIBER HOLE TILT : 0.5° MAX
  3. MATERIAL : POLYPHENYLENE SULFIDE

Material: SEE NOTE 3

REV.	DATE	DESCRIPTION	ECN
A	5/7/01	RELEASE TO SALES	00006
B	10/14/08	MODIFIED WINDOW TO RELECT MOLDED PART	01064

**CUSTOMER DRAWING**

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION

**METRIC/mm**

**US CONE C**

Hickory, NC  
800-769-0944  
[www.usconec.com](http://www.usconec.com)

TITLE: **FERRULE, MT, 4 FIBER, SINGLE MODE, PPS**

SIZE	S&M Part No.:	DWG NO.	REV
<b>B</b>	MTFA-4SM5-02-NBC	<b>C10497</b>	<b>B</b>
SCALE	Drafter	Date:	SHEET
N.T.S.	F. COPE	10/10/2000	1 OF 1

TP04SPA-2