

NOTES:

1. THIS DIMENSION (7± 0.1) TO BE HELD FOR LENGTH OF 0.3 MIN FROM FRONT SHOULDER. REMAINDER TO BE FLUSH OR BELOW SURFACE, DOWN TO 6.40 MIN.
2. $\varnothing 0.1253$ GO, $\varnothing 0.1260$ NO GO WITH THE WEIGHT OF 50g FIBER HOLE ECCENTRICITY: 0.9 μ m MAX.
3. MATERIAL: PPS


USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: SEE NOTES

REV	DATE	DESCRIPTION	ECN
A	2/19/09	INITIAL RELEASE	01116
B1	8/30/13	6.40 MIN SEE NOTE 1 WAS 6.45±0.05; NOTE 1 "...DOWN TO 6.40 MIN." WAS "...DOWN TO 6.45 MIN."	01632
B	9/4/13	RELEASE	01632

CUSTOMER DRAWING

DIMENSIONS FOR REFERENCE ONLY



METRIC/mm



Hickory, NC
800-769-0944
www.usconec.com

TITLE
MT FERRULE, 8F-SM Elite®, PPS, GB

SIZE	S&M Part No.: B 12440	DWG NO. C12440	REV B
SCALE	N.T.S.	Drafter B. HENLEY	Date: 2/19/2009

SHEET 1 OF 1