



NOTES:

- 1. SPRING ENDS GROUND.
- 2. WHEN COMPRESSED TO 7mm LENGTH, SPRING FORCE = 23 NEWTONS.

USCONEC LTD. PROPRIETARY THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.			
Material:		STAINLESS STEEL	
REV.	DATE	DESCRIPTION	ECN
C	2/20/13	RELEASE	01553
D1	11/3/14	ADDED 4.13 DIM & DEL'D Ø0.58 DIM; LENGTH DIM "SEE NOTE 2" was 15.25; ADDED NOTE 2	1607-mm
-	4/30/15	ADDED 14 DIM.; MOVED "SEE NOTE 2" DIM'S LEADER TO COMPRESSED POS.; DEL'D "SUPERCEDES C10241" CALLOUT	1607-my
D	5/13/15	RELEASE	1607-mm

CUSTOMER DRAWING

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION

METRIC/mm

▲ DENOTES CRITICAL DIMENSION

Hickory, NC
800-769-0944
www.usconec.com

USCONEC

TITLE **SPRING, MTP®, HIGH FORCE**

SIZE	S&M Part No.:	DWG NO.	REV
B	12501	C12501	D
SCALE	Drafter	Date:	SHEET
N.T.S.	H. NGUYEN	10/12/2010	1 OF 1