



NOTES:

1. MATERIAL: POLYPHENYLENE SULFIDE RESIN
MAT'L SPEC SHEET: C7438
2. GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6980 TO 0.6990 TO MINIMIZE INSERTION LOSS.

USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: SEE NOTES

REV	DATE	DESCRIPTION	ECN
A	9/10/10	INITIAL RELEASE	01195

CUSTOMER DRAWING

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION



METRIC/mm

▲ DENOTES CRITICAL DIMENSION

Hickory, NC
800-769-0944
www.usconec.com

USCONEC

TITLE: **FERRULE, 24F, PPS, MM MT Elite®**

SIZE	S&M Part No.:	DWG NO.	REV
B	12557	C12557	A
SCALE	Drafter	Date:	SHEET
N.T.S.	M. YOUNT	10/20/2009	1 OF 1