

SECTION A-A

NOTES:

- MATERIAL: POLYPHENYLENE SULFIDE RESIN
MAT'L SPEC SHEET: C7438
- GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6980 TO 0.6990 TO MINIMIZE INSERTION LOSS.

USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: SEE NOTES


REV	DATE	DESCRIPTION	ECN
X1	8/10/10	-	01249
A	10/1/12	INITIAL RELEASE	01249
B	12/11/13	ADDED MISSING 0.500 PITCH DIMENSION	-

CUSTOMER DRAWING

USCONEC
Hickory, NC
800-769-0944
www.usconec.com

DIMENSIONS FOR REFERENCE ONLY

TITLE
FERRULE, 16F, MM MT
Elite®, PPS



SIZE	S&M Part No.:	DWG NO.	REV
B	13226	C13226	B

METRIC/mm

SCALE	Drafter	Date:	SHEET	OF
N.T.S.	B. HENLEY	8/10/2010	1	1

▲ DENOTES CRITICAL DIMENSION