

NOTES:

- 1. SPRING ENDS GROUND
- 2. WHEN COMPRESSED TO 7mm LENGTH, SPRING FORCE = 9.8 NEWTONS.


USCONEC LTD. PROPRIETARY
 THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: STAINLESS STEEL

REV	DATE	DESCRIPTION	ECN
A	3/19/12	INITIAL RELEASE	01402
B1	10/5/15	ADD DIM 4.24 & DEL DIM Ø0.56; ADD NOTE 2	1835-mm
B	10/16/15	RELEASE	1835-mm
C1	4/7/16	4.23 W 4.24	1916-mm
C	4/26/16	RELEASE	1916-mm

CUSTOMER DRAWING

DIMENSIONS FOR REFERENCE ONLY



METRIC/mm

▲ DENOTES CRITICAL DIMENSION

USCONEC
 Hickory, NC
 800-769-0944
www.usconec.com

TITLE
 SPRING, MTP®,
 HIGH FIBER COUNT, 9.8N

SIZE	S&M Part No.:	DWG NO.	REV
B	14511	C14511	C
SCALE	Drafter	Date:	SHEET
N.T.S.	M. YOUNT	3/8/2012	1 OF 1