



NOTES:

1. $X_i = (2i - n - 1) \times 0.125$, WHERE i CORRESPONDS TO THE 'i' TH FIBER PER THE NUMBERING CONVENTION, AND n IS THE TOTAL NUMBER OF FIBERS IN THE ARRAY.
2. NOMINAL TRUE POSITION OF FIBER-HOLE CENTERS IS SHIFTED IN THE 'Y' DIRECTION (TOWARD THE NON-WINDOW SIDE) TO ACCOUNT FOR FERRULE TRANSLATION DUE TO THE 8° ANGLE.
3. MATERIAL: POLYPHENYLENE SULFIDE RESIN, MAT'L SPEC SHEET #C7438
4. GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6984 TO 0.6986 TO MINIMIZE INSERTION LOSS.

USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: SEE NOTES

REV	DATE	DESCRIPTION	ECN
X1	2/22/12	---	01429
A	6/14/12	RELEASE	01429

CUSTOMER DRAWING

▲ DENOTES CRITICAL DIMENSION

USCONEC
Hickory, NC
800-769-0944
www.usconec.com

DIMENSIONS FOR REFERENCE ONLY

TITLE
FERRULE, 12F, PPS,
SM MT Elite® Pre-Angled

THIRD ANGLE PROJECTION

SIZE S&M Part No.: 14620 DWG NO: **C14620** REV: A

METRIC/mm

SCALE N.T.S. Drafter: M.McCROSKY Date: 2/22/2012 SHEET 1 OF 1