

**NOTES:**

1. WHEN COMPRESSED TO 6.5mm LENGTH, SPRING FORCE = 9.8 NEWTONS.


**USCONEC LTD. PROPRIETARY**  
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

**Material:** STAINLESS STEEL

REV	DATE	DESCRIPTION	ECN
X1	4/30/15	---	1607-my
A	5/13/15	INITIAL RELEASE	1607-mm

**CUSTOMER DRAWING**

DIMENSIONS FOR REFERENCE ONLY



**METRIC/mm**



Hickory, NC  
800-769-0944  
[www.usconec.com](http://www.usconec.com)

**TITLE**  
SPRING, OVAL, MTP®  
DEMAGNETIZED

SIZE	S&M Part No.:	DWG NO.	REV
<b>B</b>	15399	<b>C15399</b>	<b>A</b>
SCALE	Drafter	Date:	SHEET
N.T.S.	M.McCROSKEY	11/3/2014	1 OF 1

▲ DENOTES CRITICAL DIMENSION