



**NOTES:**

- $X_i = (2i - n - 1) \times 0.125$ , WHERE  $i$  CORRESPONDS TO THE  $i$ 'TH FIBER PER THE NUMBERING CONVENTION, AND  $n$  IS THE TOTAL NUMBER OF FIBERS IN THE ARRAY (12 FIBERS TOTAL IN THE CASE OF THIS 4+4 FERRULE).
- MATERIAL: POLYPHENYLENE SULFIDE RESIN, MAT'L SPEC #C7718
- GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6980 TO 0.6990 TO MINIMIZE INSERTION LOSS

**USCONEC LTD. PROPRIETARY**  
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

**Material: SEE NOTES**

REV	DATE	DESCRIPTION	ECN
X1	7/23/15	-	1745-mc
X2	2/11/16	ADDED NOTES; ADDED FEATURES	1745-my
A	3/22/16	INITIAL RELEASE	1745-mm

**CUSTOMER DRAWING**  
DIMENSIONS FOR REFERENCE ONLY  
THIRD ANGLE PROJECTION  
**METRIC/mm**

▲ DENOTES CRITICAL DIMENSION

**USCONEC** Hickory, NC  
800-769-0944  
www.usconec.com

**TITLE**  
FERRULE, 4+4, PPS,  
MM MT ELITE®

SIZE	S&M Part No.:	DWG NO.	REV
B	16519	<b>C16519</b>	A
SCALE	Drafter	Date:	SHEET
N.T.S.	M. CLOUD	7/23/2015	1 OF 1