



**NOTES:**

- $X_i = (2i - n - 1) \times 0.125$ , WHERE  $i$  CORRESPONDS TO THE  $i$ 'th FIBER PER THE NUMBERING CONVENTION, AND  $n$  IS THE TOTAL NUMBER OF FIBERS IN THE ARRAY.
- MATERIAL: POLYPHENYLENE SULFIDE RESIN, MAT'L SPEC #C7438
- GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6980 TO 0.6990 TO MINIMIZE INSERTION LOSS

**USCONEC LTD. PROPRIETARY**  
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

**Material:** SEE NOTES

REV	DATE	DESCRIPTION	ECN
X1	12/6/16	-	my
A	1/18/17	INITIAL RELEASE	2007-mm

**CUSTOMER DRAWING**  
DIMENSIONS FOR REFERENCE ONLY  
THIRD ANGLE PROJECTION

**METRIC/mm**

▲ DENOTES CRITICAL DIMENSION

**USCONEC**  
Hickory, NC  
800-769-0944  
[www.usconec.com](http://www.usconec.com)

**TITLE**  
FERRULE, 24F, PPS,  
MM MT Elite® W/ DIMPLES

SIZE	S&M Part No.:	DWG NO.	REV
B	17794	<b>C17794</b>	A
SCALE	Drafter	Date:	SHEET
N.T.S.	M. YOUNT	12/6/2016	1 OF 1