



**NOTES:**

1. WHEN COMPRESSED TO 7mm LENGTH,  
SPRING FORCE = 20 NEWTONS.

**USCONEC LTD. PROPRIETARY**  
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED  
INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR  
OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

**Material: STAINLESS STEEL**

REV	DATE	DESCRIPTION	ECN
X1	8/11/16	--	1974-mm
A	8/31/16	INITIAL RELEASE	1974-mm
B	1/11/17	CORRECTION: DELETED "SPRING ENDS GROUND" NOTE	1974-my

**CUSTOMER DRAWING**

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION

**METRIC/mm**

▲ DENOTES CRITICAL DIMENSION

Hickory, NC  
800-769-0944  
[www.usconec.com](http://www.usconec.com)

**USCONEC**

TITLE **SPRING, MTP®, 20N**

SIZE	S&M Part No.:	DWG NO.	REV
<b>B</b>	17881	<b>C17881</b>	<b>B</b>
SCALE	Drafter	Date:	SHEET
N.T.S.	M.McCROSKEY	8/11/2016	1 OF 1