

NOTES:

1. MATERIAL: POLYPHENYLENE SULFIDE RESIN  
MAT'L SPEC SHEET: C7438
2. GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6980 TO 0.6990 TO MINIMIZE INSERTION LOSS.


**USCONEC LTD. PROPRIETARY**  
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

**Material:** SEE NOTES

REV	DATE	DESCRIPTION	ECN
C	4/3/09	CHANGED TITLE TO FERRULE, 12F, MM MT ELITE®, PPS	01129
D	11/9/09	ADDED NOTE 3	01195
E	5/3/10	CHANGED OPTIONAL I.D. TO "ME 12"; DEL. NOTE 3 ADDED BOOT STOP AND CORNER RADII TO INSIDE OF FERRULE	01195
F	4/25/11	ADDED 3.5 AND 1.7 DIMS	01302

**CUSTOMER DRAWING**

DIMENSIONS FOR REFERENCE ONLY



Hickory, NC  
800-769-0944  
www.usconec.com

TITLE  
**FERRULE, 12F, PPS,  
MM MT Elite®**

SIZE	S&M Part No.:	DWG NO.	REV
B	9724	<b>C9724</b>	F
SCALE	Drafter	Date:	SHEET
N.T.S.	M. YOUNT	2/6/2008	1 OF 1

▲ DENOTES CRITICAL DIMENSION

**SECTION A-A**