



GATE VESTIGE MAY BE PRESENT
IN ONE OR BOTH LOCATIONS SHOWN

SECTION A-A

- NOTES:
- $X_i = (2i - n - 1) \times 0.125$, WHERE i CORRESPONDS TO THE i 'th FIBER PER THE NUMBERING CONVENTION, AND n IS THE TOTAL NUMBER OF FIBERS IN THE ARRAY.
 - NOMINAL TRUE POSITION OF FIBER-HOLE CENTERS IS SHIFTED IN THE 'Y' DIRECTION (TOWARD THE NON-WINDOW SIDE) TO ACCOUNT FOR FERRULE TRANSLATION DUE TO THE 8° POLISH ANGLE.
 - MATERIAL: POLYPHENYLENE SULFIDE RESIN, MAT'L SPEC SHEET #C7718
 - GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.698 TO 0.699 TO MINIMIZE INSERTION LOSS.

USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: SEE NOTE 3

REV	DATE	DESCRIPTION	ECN
B	10/14/08	MODIFIED WINDOW TO RELECT MOLDED PART	01064
C1	12/21/09	CHANGED 0.700 ± 0.001 TO 0.699 - 0.700	01207
C2	3/8/18	REVISED DWG. TO STD. FORMAT	1207-rr.my
C	10/25/18	RELEASED	1207-rr
D	2/13/20	REVISED GATE VESTIGE CALLOUT	2247-my

CUSTOMER DRAWING

USCONEC Hickory, NC
800-769-0944
www.usconec.com

TITLE: **FERRULE, 4F, PPS, SM**

▲ DENOTES CRITICAL DIMENSION

SIZE	S&M Part No.:	DWG NO.	REV
B	MTFA-4SM5-02-NBC	C10497	D
SCALE	Drafter	Date:	SHEET
N.T.S.	F. COPE	10/10/2000	1 OF 1

METRIC/mm