



**NOTES:**

1.  $X_i = (2i - n - 1) \times 0.125$ , WHERE  $i$  CORRESPONDS TO THE  $i$ 'th FIBER PER THE NUMBERING CONVENTION, AND  $n$  IS THE TOTAL NUMBER OF FIBERS IN THE ARRAY
2. MATERIAL: POLYPHENYLENE SULFIDE RESIN, MAT'L SPEC #C7438
3. GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.5480 TO 0.5490 TO MINIMIZE INSERTION LOSS

**USCONEC LTD. PROPRIETARY**  
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

**Material:** SEE NOTES

REV	DATE	DESCRIPTION	ECN
X2	4/5/16	ADDED NOTE 1; ADDED GD&T; STANDARDIZED DIM. FORMAT	1528-my
A	9/9/16	POSITIONAL TOL. Ø0.003 was Ø0.0026; REMOVED GD&T FOR Ø549 - 0.550	1970-mm
		INITIAL RELEASE	
B1	9/27/17	DEL'D FIBER HOLE TRUE POS. SPEC	2048-rr
B	10/20/17	RELEASE	2048-rr

**CUSTOMER DRAWING**

**USCONEC**  
Hickory, NC  
800-769-0944  
www.usconec.com

DIMENSIONS FOR REFERENCE ONLY

**TITLE**  
FERRULE, 16F, PPS, MM MT Elite®



SIZE	S&M Part No.:	DWG NO.	REV
B	15905	<b>C15905</b>	B
SCALE	Drafter	Date:	SHEET
N.T.S.	B. HENLEY	5/30/2014	1 OF 1

**METRIC/mm**

▲ DENOTES CRITICAL DIMENSION

**SECTION A-A**