



- NOTES:**
- $X_i = (2i - n - 1) \times 0.125$ , WHERE  $i$  CORRESPONDS TO THE  $i$ 'th FIBER PER THE NUMBERING CONVENTION, AND  $n$  IS THE TOTAL NUMBER OF FIBERS IN THE ARRAY.
  - NOMINAL TRUE POSITION OF FIBER-HOLE CENTERS IS SHIFTED IN THE 'Y' DIRECTION (TOWARD THE NON-WINDOW SIDE) TO ACCOUNT FOR FERRULE TRANSLATION DUE TO THE 8° ANGLE.
  - MATERIAL: POLYPHENYLENE SULFIDE RESIN, MAT'L SPEC SHEET #C7718
  - GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6984 TO 0.6986 TO MINIMIZE INSERTION LOSS.

**USCONEC LTD. PROPRIETARY**  
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

**Material:** SEE NOTES

REV	DATE	DESCRIPTION	ECN
	8/1/18	INITIAL RELEASE	2123-rr
X1	11/13/19	REVISED GATE VESTIGE CALLOUT & CENTERED '8'	2123-mm my
A	11/13/19	INITIAL RELEASE	2123-rr

▲ DENOTES CRITICAL DIMENSION

**CUSTOMER DRAWING**

**USCONEC** Hickory, NC  
800-769-0944  
www.usconec.com

**TITLE**  
FERRULE, 8F, PPS, SM MT Elite®,  
PRE-ANGLED

SIZE: B S&M Part No.: 16338 DWG NO: C16338 REV: A

SCALE: N.T.S. Drafter: R. RAWALD Date: 8/2/2018 SHEET 1 OF 1

**METRIC/mm**

