



NOTES:

1. $X_i = (2i - n - 1) \times 0.125$, WHERE i CORRESPONDS TO THE 'i'th FIBER PER THE NUMBERING CONVENTION, AND n IS THE TOTAL NUMBER OF FIBERS IN THE ARRAY.
2. MATERIAL: POLYPHENYLENE SULFIDE RESIN, MAT'L SPEC #C7438
3. GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6980 TO 0.6990 TO MINIMIZE INSERTION LOSS.

USCONEC LTD. PROPRIETARY			
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.			
Material:		SEE NOTES	
REV.	DATE	DESCRIPTION	ECN
B1	9/27/17	DEL'D FIBER HOLE TRUE POS. SPEC	2048-rr
B	10/20/17	RELEASE	2048-rr
C	4/17/24	HID TANGENT EDGES IN REAR VIEW TO BETTER REFLECT MOLDED PART	

CUSTOMER
DRAWING

DIMENSIONS FOR REFERENCE
ONLY

THIRD ANGLE PROJECTION

METRIC/mm

USCONEC

Hickory, NC
800-769-0944
www.usconec.com

TITLE
FERRULE, 12F, PPS,
MM MT Elite® W/ DIMPLES

SIZE
B

S&M Part No.:
17184

DWG NO.
C17184

SCALE
N.T.S.

Drafter
M.McCROSKEY

Date:
1/11/2016

SHEET
1

OF
1

▲ DENOTES CRITICAL DIMENSION