



NOTES:

- 1. WHEN COMPRESSED TO 6.7mm LENGTH, SPRING FORCE = 19.5 NEWTONS

USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: STAINLESS STEEL

REV	DATE	DESCRIPTION	ECN
X1	4/27/16	-	1927-my
A	6/28/16	INITIAL RELEASE	1927-mm
B1	3/13/18	CHANGED LENGTH DIM FROM NOMINAL TO MAX	2095-mm
B	4/2/18	RELEASE	

CUSTOMER DRAWING

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION

METRIC/mm

▲ DENOTES CRITICAL DIMENSION

Hickory, NC
800-769-0944
www.usconec.com

USCONEC

TITLE: **SPRING, UNIVERSAL, 20N, MTP®**

SIZE	S&M Part No.:	DWG NO.	REV
B	17698	C17698	B
SCALE	Drafter	Date:	SHEET
N.T.S.	M. YOUNT	4/27/2016	1 OF 1