



NOTES:

- $X_i = (2i - n - 1) \times 0.125$, WHERE i CORRESPONDS TO THE i 'TH FIBER PER THE NUMBERING CONVENTION, AND n IS THE TOTAL NUMBER OF FIBERS IN THE ARRAY.
- MATERIAL: POLYPHENYLENE SULFIDE RESIN, MAT'L SPEC #C7438
- GUIDE PINS SHOULD HAVE A DIAMETER RANGING FROM 0.6980 TO 0.6990 TO MINIMIZE INSERTION LOSS

USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: SEE NOTES

REV	DATE	DESCRIPTION	ECN
X1	12/6/16	-	my
A	1/18/17	INITIAL RELEASE	2007-mm
B1	9/27/17	DEL'D FIBER HOLE TRUE POS. SPEC	2048-rr
B	10/20/17	RELEASE	2048-rr

CUSTOMER DRAWING

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION



METRIC/mm

▲ DENOTES CRITICAL DIMENSION

USCONEC
Hickory, NC
800-769-0944
www.usconec.com

TITLE
FERRULE, 24F, PPS,
MM MT Elite® W/ DIMPLES

SIZE	S&M Part No.:	DWG NO.	REV
B	17794	C17794	B
SCALE	Drafter	Date:	SHEET
N.T.S.	M. YOUNT	12/6/2016	1 OF 1