



NOTES:

1. WHEN COMPRESSED TO 6.7mm LENGTH, SPRING FORCE = 3.1 NEWTONS

USCONEC LTD. PROPRIETARY
THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.

Material: STAINLESS STEEL

REV	DATE	DESCRIPTION	ECN
X1	10/12/18	-	2025-mm
A	1/24/19	INITIAL RELEASE	
B	1/29/19	NO PART CHG. - DIM CORRECTION: 5.55 w 5.60	2025-my

CUSTOMER DRAWING

DIMENSIONS FOR REFERENCE ONLY

THIRD ANGLE PROJECTION

METRIC/mm

▲ DENOTES CRITICAL DIMENSION

Hickory, NC
800-769-0944
www.usconec.com

USCONEC

TITLE
SPRING, 3.1N, UNIVERSAL, MXC® / PRIZM® MT, SPACER

SIZE	S&M Part No.: B 19326	DWG NO. C19326	REV B
SCALE	Drafter M.McCROSKEY	Date: 10/11/2018	SHEET 1 OF 1