



NOTES:

- 1. RECOMMENDED CABLE DIAMETER = 3.2mm MAX

▲ DENOTES CRITICAL DIMENSION

<p>USCONEC LTD. PROPRIETARY THIS DOCUMENT AND THE ASSOCIATED DATA CONTAIN RESTRICTED INFORMATION THAT IS USCONEC LTD. PROPERTY. DISCLOSE OR DUPLICATE FOR OTHERS ONLY AS AUTHORIZED BY USCONEC LTD.</p>				<p>CUSTOMER DRAWING</p>		<p>USCONEC Hickory, NC 800-769-0944 www.usconec.com</p>			
<p>Material: PP / MAT'L SPEC #C13102, BLACK</p>				<p>DIMENSIONS FOR REFERENCE ONLY</p>		<p>TITLE BOOT, PUSH-PULL, MTP® PRO</p>			
REV	DATE	DESCRIPTION	ECN	<p>THIRD ANGLE PROJECTION</p>		SIZE	S&M Part No.:	DWG NO.	REV
X1	1/28/20	----		2268-mm		A3	21442	C21442	A
A	5/1/20	ADDED SPINE FEATURE CALLOUT				SCALE	Drafter	Date:	
		INITIAL RELEASE				N.T.S.	M.McCROSKEY	1/28/2020	
				METRIC/mm				SHEET	1 OF 1